



INTERMEDIATE PRESSURE LIMITS
 INTERMEDIATE PRESSURES MUST BE
 BETWEEN 125-145 PSIG AT BOTH 300 AND
 3300 PSIG. 0 PSIG INTERMEDIATE
 PRESSURE CREEPAGE ALLOWED AFTER
 SEATING OF A NEW SEAT.

ITEM NO.	QTY REQD	PART NO.	DESCRIPTION	SUGG. RETAIL
1	1	10-101-130	YOKE SCREW, 3/8 THREAD	
	1	10-101-113	YOKE SCREW, 7/16 THREAD	
	1	10-101-132	YOKE SCREW, 9/16 THREAD	
2	1	10-107-104	RETAINER, OSCILLATOR	
3	2	01-050-177	O-RING (BLUE)	
4	1	01-020-106	SPRING	
5	1	10-107-006	OSCILLATOR ASSY.	
6	1	01-050-322	O-RING (WHITE & BLACK)	
7	1	01-050-152	O-RING (BLACK)	
8	1	10-101-110	1ST STAGE INLET PROTECTOR	
9	1	01-050-342	O-RING (PURPLE)	
10	1	10-101-144	H.P. ADAPTER W/O O-RING, LG. MALE/SM. FEMALE THD.	
11	1	10-101-044	H.P. ADAPTER W/O-RING, LG. MALE/SM. FEMALE THD.	
12	1	10-101-138	H.P. ADAPTER W/O O-RING, LG. MALE/SM. FEMALE THD.	
13	1	01-050-138	O-RING (BLUE)	
14	1	10-101-038	H.P. ADAPTER W/O O-RING, LG. MALE/SM. FEMALE THD.	
15	1	10-101-139	PLUG, 7/16 - 20, H.P.	
16	1	10-101-039	PLUG, W/O-RING, 7/16 - 20, H.P.	
17	1	10-101-106	SEAT RETAINER	
18	1	01-050-157	O-RING (RED)	
19	1	10-101-151	SEAT, CAVE CONE	
20	1	01-050-147	O-RING (PURPLE)	
21	1	01-006-113	DECAL	
22	1	01-006-120	DECAL, WARNING	
23	1	10-107-005	BODY & YOKE SCR. SET, 9/16 THREAD	
24	2	01-050-124	O-RING (BLUE)	
25	1	10-107-107	SPRING PAD	
26	1	01-020-107	SPRING	
27	1	10-107-108	STEM	
28	1	10-107-109	RETAINER, STEM	
29	1	01-050-136	O-RING (GRAY)	
30	3	01-060-101	WASHER	
31	1	10-101-002	SPRING	
32	1	10-101-003	PISTON	
33	1	01-050-184	O-RING (RED)	
34	1	10-107-103	RETAINER, PISTON	
35	1	01-050-132	O-RING (BLUE)	
36	1	10-101-104	PLUG	
37	1	10-101-006	PLUG W/O-RING	
38	1	01-073-101	RETAINER	
39	1	01-028-101	FILTER	
40	1	01-050-144	O-RING (BLUE)	
41	1	10-107-111	ADAPTER, FRENCH	
42	1	01-028-109	FILTER, CONICAL	
43	1	10-200-008	YOKE SCREW ASSY. 9/16 THREAD	
44	1	41-035-000	ENVIRONMENTAL SILICONE, 7 GR.	
45	1	41-910-107	REPAIR PROCEDURES	
46	1	45-107-101	MANUAL	
47	-	10-107-040	REPAIR KIT, ANNUAL	

PRICES SUBJECT TO CHANGE
 WITHOUT NOTICE.

NOTES:

● NOT SHOWN

△ OPTIONAL ITEM

△ OLDER CONFIGURATION

△ FOR OLDER CONFIGURATION

H.P. HOSES USED W/NEW
 CONFIGURATION REGULATORS

△ NOT COVERED UNDER WARRANTY

△ MAXIMUM 3 WASHERS P/N 01-060-101
 WASHERS ARE USED AS SHIMS TO ADJUST
 THE INTERMEDIATE PRESSURE TO BE
 WITHIN THE SPECIFIED LIMITS.

◇ ANNUAL REPLACEMENT

◇ DYNAMIC O-RING REPLACE ANNUALLY

<> TORQUE IN INCH POUNDS

MARK 7 FIRST STAGE REGULATOR

SCUBAPRO®

CAT. NO. 10-107-000

P	JULY '88	CONFIGURATION 11
REV.	DATE	