



**INTERMEDIATE PRESSURE LIMITS**  
 INTERMEDIATE PRESSURES MUST BE  
 BETWEEN 125-145 PSIG AT BOTH 300  
 AND 3300 PSIG. 0 PSIG INTERMEDIATE  
 PRESSURE CREEPAGE ALLOWED AFTER  
 SEATING OF A NEW SEAT.

ITEM NO.	CAT NO.			PART NO.	DESCRIPTION
		10-400-000	10-500-000		
				10-400-000	MARK IX FIRST STAGE REGULATION
				10-500-000	MARK X FIRST STAGE REGULATOR
ITEM NO.		QTY REQD.		PART NO.	DESCRIPTION
1		1	1	10-107-111	ADAPTER, FRENCH
2		1	1	01-050-144	O-RING (BLUE)
3		1	1	01-073-101	RETAINER
4		1	1	01-028-109	FILTER, CONICAL
5		1	1	10-400-104	YOKE RETAINER
6		3	3	01-050-138	O-RING (BLUE)
7		1	1	10-101-132	YOKE SCREW, 9/16 THREAD
8		-	1	01-006-510	DECAL, MK10
9		1	1	10-200-008	YOKE SCREW ASSY., 9/16 THREAD
10		1	1	10-101-131	YOKE, 9/16 THREAD
11		1	1	10-101-111	1ST STAGE INLET PROTECTOR
12		1	1	10-101-106	SEAT RETAINER
13		1	1	01-050-157	O-RING (RED)
14		1	1	10-101-151	SEAT, CAVE CONE
15		1	1	01-050-147	O-RING (PURPLE)
16		1	1	10-400-103	SADDLE
17		1	1	10-500-108	BODY
18		1	1	10-101-044	H.P. ADAPTER W/O-RING, LG. MALE/SM. FEMALE THD.
19		1	1	01-050-342	O-RING (PURPLE)
20		1	1	10-101-144	H.P. ADAPTER W/O O-RING, LG. MALE/SM. FEMALE THD.
21		2	2	10-101-139	PLUG, 7/16-20 H.P.
22		2	2	10-101-039	PLUG, W/O-RING, 7/16-20 H.P.
23		1	1	01-050-137	O-RING (AMBER)
24		3	3	01-060-101	WASHER
25		1	1	10-400-004	SPRING
26		1	1	10-500-003	PISTON
27		1	1	01-050-162	O-RING (AMBER)
28		1	1	01-050-217	O-RING (BLUE)
29		-	1	10-500-103	RETAINER, SWIVEL
30		-	1	01-060-500	WASHER
31		-	1	10-500-101	CAP, SWIVEL
32		-	1	01-050-161	O-RING (BLUE)
33		-	1	10-500-102	SWIVEL, 5 PORT
34		-	1	10-500-005	SWIVEL & RETAINER SET
35		4	4	10-101-104	PLUG
36		4	4	01-050-132	O-RING (BLUE)
37		4	4	10-101-006	PLUG W/O-RING
38		1	-	10-400-105	CAP, 5 PORT
39		1	1	01-060-501	WASHER, DIN
40		1	1	10-105-117	KNOB, DIN, 200 BAR
41		1	1	10-105-118	KNOB, DIN, 300 BAR
42		1	1	10-400-106	RETAINER, DIN, 200 BAR
43		1	1	10-400-107	RETAINER, DIN, 300 BAR
44		1	1	01-050-193	O-RING (BLACK)
45		1	1	10-400-020	KIT, CONVERSION, DIN, 200 BAR
46		1	1	10-400-030	KIT, CONVERSION, DIN, 300 BAR
●		1	1	41-035-000	ENVIRONMENTAL SILICONE
●		1	1	45-500-101	MANUAL
●		-	-	10-500-040	REPAIR KIT, ANNUAL

PRICES SUBJECT TO CHANGE WITHOUT NOTICE  
 NOTES:

- NOT SHOWN
- △ OPTIONAL ITEM
- △ NOT COVERED UNDER WARRANTY
- △ FOR OLDER CONFIGURATION H.P. HOSES

△ MAXIMUM 3 WASHERS P/N 01-060-101  
 WASHERS ARE USED AS SHIMS TO ADJUST  
 THE INTERMEDIATE PRESSURE TO BE  
 WITHIN THE SPECIFIED LIMITS.  
 ◇ DYNAMIC O-RING REPLACE ANNUALLY  
 <> ANNUAL REPLACEMENT  
 TORQUE IN INCH POUNDS

## MARK 9 AND 10 FIRST STAGE REGULATORS

C	JAN '91	CONFIGURATION
Rev.	Date	10-400-000 6 10-500-000 5

# SCUBAPRO®

CAT. NO. 10-400-000  
 10-500-000